

APPROVED LIST OF PROPRIETARY CONTROL PANELS WITH AUTONOTIFICATION AND PUMP SHUTDOWN FOR TREATMENT OR DISINFECTION FAILURE

The following control panels have been approved for use with aerobic treatment units. Other panels may be suitable for Williamson County; however, supporting documentation and a demonstration will be required before approval of planning material can be granted. Any changes to these control panels will require evaluation by the Williamson County & Cities Health District.

Aerobic Pump and Controls (name change to Control Panels USA, March/2008)

ChlorAlarm CAF 300TWC-4B-115VAC or CA(2) 300TWC-4B-115VAC

CAF 300TAWC-4B-115VAC or CA(2) 300TAWC-4B-115VAC

(multiple system compatible)

CA300DPXT-5B-11VAC (Total Control for duplex pumps with lock on alarm)

Aerobic Pump and Controls (no longer being manufactured March/2008)

Proline ChlorAlarm PLCA300TLWC-3B-115VAC with ANTX TD8 auto dialer

(Proline)

PL202DPXT-5B-111VAC (Total Control! for Duplex pumps with alarm lock on)

Advanced Aerobic Programmer

Model 206 / PC-3BTAPC (AquaSafe) (digital auto dialer included)

Model 215 / PC-3BTAPC (Jet) (digital auto dialer included)

(multiple unit compatible)

Clearstream

Control Board # 207 C/T Module C/T-D207NPA (dosing cycles)

Control Board # 207 C/T Module C/T-NS207NPA (Night Spray)

Internal or external RMS100, wireless plug in RMSYS RMS308 or internal mount +.03
9-+8*6RMS300, 306

Ecological Tanks, Inc.

Model 206 (contains US Controls digital auto dialer)

Model 207 ([United Security Products](#) AVD-45b voice auto dialer)

Model 214 (USES auto dialer & timed pump control)

Model 215 (United Security Products AVD-45b voice auto dialer & timed pump control)

Model 205 (no auto dialer included, approved with attached RMS 100 auto dialer)

(AquaSafe, AquaAire)

HOOT SYSTEMS

HOOT panels are compatible on HOOT systems only. Hoot 2000 Control Panel with Radio Shack Voice Auto dialer. Requires software:

6.01 & 6.04 standard spray chip and enables Chlorine Shutdown Feature with R-24 Cut

6.24 standard Drip chip without chlorine shutdown

6.24c is Drip Chip with Chlorine shutdown without cut resistors

6.64 Liquid Chlorinator chip enables the Chlorine Shutdown Feature with R-24 Cut

6.05 & 6.08 5 light panel spray chip with RMS-300/312 autodialer

6.25c or 6.28c drip with chlorine shutdown with RMS-300/312 autodialer

6.25 & 6.28 drip without disinfection with RMS-300/312 autodialer

JNM Technologies, Inc.

Drip Tech Bioline Dosing Management Controller "W" variant, with RJR Stand-Alone Auto-Dialer

Norweco

"Integrated Systems Control Panel" with blue light & analog voice auto dialer
For use on Norweco systems only.

Proline

SPI-P500A-WC

BIO/SPI Septic Products Inc.

BIO 500AD (AquaKlear)(digital auto dialer included)

50B001-AD-WC (AquaKlear)

80000-130-WC (Pro Flo)

50B138-A-AV-WC (Bio-Robix, Nu Water)(with RMSYS 100 or RMYSYS 300 digital autodialer)

SJE Rhombus

Model Pro 11-115

Model Pro 11-237 (new) United Security Products, AVD-45b Automatic Voice dialer (Southern)

RJR Controls

Model AN4080FSSTT (Nayadic digital auto dialer included)

Model ACP-JT FAILSAFE (Jet digital auto dialer included)

Model ACP-PCTF (AquaKlear RJR Controls auto dialer)

Control Panels USA Inc.

P111-T6A1-B (vacuum device aerators)

(multiple system compatible)

P111-T10A1S1-B (compressors used for aeration)

(multiple system compatible)

(duplex controls & multiple aerator panels available)